

Insulated Glazed Sectional Door



Supplied with aluminium framed glazed panel and micro ribbed bottom panel.

Micro ribbed bottom panel

Sandwich panel with CFC and ITCFC free foam, micro ribbed profile RAL9006 732mm as standard up to 5000mm wide. 610mm deep panels used above 5000mm due to ease of handling, optional section heights of 610mm and 488mm.

Glazing

Single or double glazing transparent or stucco embossed sandwich panels.

Push pull

Manual operation, doors up to 3000mm x 3000mm supplied with pull chain. Doors in excess of 3000mm x 3000mm come with chain hoist. Manual doors come with footstep handle and spring loaded shootbolt.

3 phase electrical operation is also available with Direct Drive. Pre-wired to starter with push button station.

Single phase electrical operation is also available with Direct Drive. Pre-wired to starter with push button station.

We can provide a variety of activation methods depending on site conditions and usage. These include:

- Induction loops
- Remote control
- Radar operation
- Timed and close
- Key switch push buttons
- Reflective photobeams

Seals - flexible rubber seals fitted to all 4 sides.

Safety features – cable and springbreak devices

As well as STD RAL 9006 at extra cost doors can be supplied in a full range of RAL colours.

For further details of these products, please contact Zenith and we will be pleased to send you further detailed information.